Neata® Super energy

Lithium Battery Series

LFP2460(25.6V60AH)



Lithium Series Batteries provide superior performance, capacities and reliability. Using state of high power cell technology the lithium series is designed for environmentally sensitive areas that require enhanced cycle life capabilities in commercial, industrial, residential, and private applications. The maintenance free construction and advanced design features makes the lithium Series the definitive choice for a wide variety of markets; Solar and Renewable Energy Storage; Electric Vehicle and Golf cart; Industrial equipment, Floor Machines,Forklifts, Aerial lifts, and Robotics; Marine, RV,and no-idle solutions; Mobility and Medical Equipment; Telecom, Broadband and Cable TV; UPS systems.

Applications



BATTERY SPECIFICATIONS

Battery Type - Chemistry	LiFePO4		Internal Resistance - Milliohms	< 80	mΩ
Nominal Voltage	25.6	V	Efficiency - round trip	> 99.5	%
Amp Hour Capacity	60	AH	Self Discharge per Month	< 3	%
Energy Density	1536	Wh	Max parallel connections	4	pcs
Dimensions(LxWxH)	260x180x257	mm	Seriesl connections	51.2	V
Weight	17.5	KGS	Case IP Rating	IP56	
Terminal Type	M8		DesignLife	20	Years
Terminal Torque	12.4	NM	Cycle Life (1C, 25℃@80%DOD)	>4000	cycles
Case Material	ABS		Cycle Life (0.2C, 25℃@80%DOD)	>6000	cycles
BMS build-in	Yes				
			Discharge Temperature	(-23 to 65)	℃
Recommend Charge Voltage	28.5	±0.20V	Charge Temperature	(-3 to 65)	℃
Max Charge Voltage	29.5	±0.20V	Storage Temperature	(-20 to 45C)	℃
Recommend Charge current	25	A			
Max Charge Current	100	A	Bluetooth(APP)	Optional	
Charge Current (0 to -10℃)	<0.1	C	LCD Screen	Optional	
Charge Currrent (-20 to -10℃)	<0.05	C	Heating functions -20°C	Optional	By Charger
Recommend Discharging voltage	22.5	±0.20V	Batteryself heating function	Optional	BY Cell
Max Discharging Voltage	19.2	±0.20V			
Max Discharge Current	100	A	Shipping Classification	UN3480, CLASS 9	
Pulse Discharge Current	180	A±3S	Other Certifications	CB /CE	

Http//:www.neata-batt.com
Shenzhen Neata Power Tech co.,Ltd
FOR MORE INFORMATION, PLEASE MAIL: SALES@NEATA-BATT.COM

©2021 Neata.All right reserved.
Subject to revisions without prior notice

Neata® Super energy

Lithium Battery Series

LFP2460(25.6V60AH)

BMS SPECIFICATIONS

BMS Version :LL

BMS Protections Range: Over (Voltage, Current, Temperaturemanagement) and cell balance

Over Charging Cell protection	>3.80	±0.05V	Delay		2	±0.5S	
Over Charging Pack Warning	>29.6	±0.20V					
Over Charging Pack protection	>30	±0.20V	Delay		2	±0.5S	
Over Charging Current Warning	>105	±2.0A					
Over Charging Current protection 1	>105<125	±2.5A	Delay		15	±1.0S	
Over Charging Current protection 2	⩾125	±2.5A	Delay		3	±1.0S	
OverCharging Temp Protection 1	<-5 or>70	±3℃	Release	>0 or < 60		±3℃	Delay:2±0.5S
Over Discharging Cell protection	<2.1	±0.05V	Delay		2	±0.5S	
Over Discharging Pack protection	<19.2	±0.20V	Delay		2	±0.5S	
Over Discharging current Warning	>105	±2.5A					
Over Discharging current protection 1	>105 <180	±2.5A	Delay		20	±1.0S	
Over Discharging current protection 2	⩾180	±2.5A	Delay		3	±1.0S	
Over Discharging Temp Protection 1	<-25 or>75	±3℃	Release	>-20 or < 70		±3℃	
PCB Temp protection	>95	±3℃	Release	< 80		±3℃	Delay:2±0.5S
Cell Balance Start	3.5	±0.05V	Cell voltage difference < 20mV				Passive balance
Balance Current	150	±10mA					
Short circuit			Delay		0.1	±0.2ms	
Power consumption	<300	uA	Switch-off mode			Storage & transportation	
	<500	uA	Sleep mode			Protection & stand-by	
	<15	mA	Operating mode			Operating	
	<28	mA	Operating mode			Low voltage to start Pre-charge	
Communication ports	Major CAN/RS485 opitional for Bluetooth/Dryport/SNMP					Can be customized	
Temperature accuracy	±2	℃	Measuring range -40~100℃				
Voltage accuracy	±15	mv	For cells and module				
Current accuracy	FSC	±5%	Measuring range -200~+200A				
SOC	±5%		Integral calculation				

Different DOD Discharge Cycle Life Curve 1C 25℃



Different Temperature Discharge Curve(0.2C)



State of Charge Curve(0.5C, 25℃)



Http//:www.neata-batt.com
Shenzhen Neata Power Tech co.,Ltd
FOR MORE INFORMATION, PLEASE MAIL: SALES@NEATA-BATT.COM

©2021 Neata.All right reserved.
Subject to revisions without prior notice